

RESIDENTIAL
BOILER
SYSTEMS

BYM-SE Series / Standart Efficiency Wall Hung Gas Boiler (BYM-SE 24)



Digital
LCD
Display
Panel

Compact
Dimensions

Fault
Detection
System

Brass
Hydraulic
Group

Stainless
Steel
Domestic
Hot Water
Heat
Exchanger

Natural
Gas
or
LPG

MODEL

BYM-SE-24 20.640 kcal/h heating capacity

boymak.com.tr

 **boymak**


BDR THERMEA GROUP

Wall Hung Gas Boiler Technical Specifications



Stainless Steel Burner Group:

Burner group appropriate for the combustion of natural gas and LPG with its stainless steel structure of the upper part is long-lasting.



Heat Exchanger:

The main heat exchanger in contact with flame is produced as fine structure since its heat resistance is higher. Thanks to this feature, temperature transferring of the gas burned in the the combustion chamber into the water passing through main heat exchanger is provided more quickly.

Technical Data Sheet

Models		BYM-SE 24 Fi
Gas category		II2H3B/P
Maximum heat load	kW	25.8
Minimum heat load	kW	13.0
Maximum heat power	kW	24.0
	kcal/h	20.640
Minimum heat power	kW	11.6
Maximum efficiency (Nominal)	%	93
Efficiency Class in accordance with 92/42/EEC Directive		★★★
Central heating system max. Pressure	bar	3
Heating circuit temperature setting range	°C	30 - 85
Hot domestic hot water circuit temperature setting range	°C	35 - 60
Expansion tank capacity	l	7
Expansion tank initial pressure	bar	1
Hot domestic hot water circuit max. pressure	bar	8
Hot domestic hot water circuit min. dynamic pressure	bar	0.15
Min. hot domestic hot water production	l/min.	2.5
Hot domestic hot water production ($\Delta T = 25^{\circ}\text{C}$)	l/min.	13.7
Flue type		C12-C32-C52-C82-B22
Special domestic hot water production (according to EN 625)	l/min.	10.7
Equiaxial flue diameter	mm	60/100
Max. flue gas flow	kg/sec.	0.014
Min. flue gas flow	kg/sec.	0.014
Flue gas max. temperature	°C	140
NOx class	-	3
Type of gas	-	Doğalgaz, LPG
Voltage	V	230
Frequency	Hz	50
Net weight	kg	38
Power consumption	W	135
Dimensions	height	725
	width	400
	depth	300
Protection class (According to EN 60529)	-	IPX 4D



BDR THERMEA GROUP

Orta Mahalle, Akdeniz Sok. No: 8 Tuzla 34959 - İSTANBUL
Tel.: +90 216 581 65 00 Faks: +90 216 581 65 82
www.baymak.com.tr

KT-24-03-14 Yayın Tarihi: 23.01.2018 Rev.No: 1 Rev.Tarih: 24.02.2023

Authorised Dealer